

TCB**GRANT OF EQUIPMENT
AUTHORIZATION****TCB****Certification****Issued Under the Authority of the
Federal Communications Commission****By:****Timco Engineering, Inc.
849 NW State Road 45
P.O. Box
370,
Newberry, FL 32669****Date of Grant: 04/21/2006****Application Dated: 04/21/2006****Kenwood USA Corporation
3970 Johns Creek Court
Suite 100
Suwanee, GA 30024****Attention: Joel Berger , Staff Engineer****NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: ALH36923130**Name of Grantee: Kenwood USA Corporation****Equipment Class: Licensed Non-Broadcast Transmitter Held to Face****Notes: UHF/FM HANDHELD TRANSCEIVER**

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
BL	90, 95A, 90.210	450.0 - 470.0	2.0	2.5 PM	16K0F3E
BL	90, 95A, 90.210	450.0 - 470.0	2.0	2.5 PM	11K0F3E

Output is at the antenna terminal of the device and must not exceed that tested for SAR compliance. This transmitter may operate with the antennas tested for this filing in Push-to-Talk, face-held and body-worn configurations. Body-worn SAR compliance is limited to the specific belt-clip and speaker/microphone configurations tested for this filing. This device must be restricted to work related operations in an Occupational/Controlled RF exposure Environment and must operate with a duty factor not exceeding 50%. All qualified end-users of this device must have the knowledge to control their exposure conditions and/or duration to comply with Occupational /Controlled SAR limit and requirements. A label, as described in this filing, must be displayed on the device to direct users to specific training information for meeting Occupational Exposure Requirements. Users must be provided with specific training information. The highest reported SAR values are - Face: 1.97 W/kg; Body: 2.75 W/kg.

This Class II Change incorporates the addition of a Lithium Ion Battery Pack to the product accessory list. The highest reported SAR values are: Face: 1.72 mW/g, Body 2.40 mW/g.

BL: The output power is continuously variable from the value listed in this entry to 45%-50% of the value listed.